

Fume-A-Vent Type 6CW 600°F Double-Ply Silicone Coated Fiberglass Hose

Date 4/13

Part No. H-06CW-XXXX

Type 6CW 600°F Hose

TAB 1-F-3

The Fume-A-Vent Type 6CW hose is made for high stress exhaust applications from spark ignition, or diesel motors. It can also be utilized in construction machines, hose reels, and other similar exhaust systems. Made with a Double-Ply Silicone Coated Fiberglass Fabric, this hose features a ThermoPlastic Abrasion Protector on the outside of its steel helix. This prevents damage to vehicles or equipment during use.

Temperature Range: - 65°F to +600°F (Baking Test)

This product meets high temperature requirements.

This product has a temperature rating at 600°F+ use for vehicle extraction systems.

This hose is made with a silver double-ply construction silicone coated fiberglass fabric hose with a silver heat-resistant fiberglass liner mechanically crimped in a continuous process. It has great flexibility and compression.

Other information available upon request. In most cases, a Fan and a Tailpipe Adaptor will be required for exhaust removal. Common lengths shown below include 15' to 30' with 4" to 8" Diameters. Other size options are always



Part No	Description	Wt. Lbs.	Bend Radius
H-6CW-0415	Fume-A-Vent 4" x 15' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	12.8	3"
H-6CW-0420	Fume-A-Vent 4" x 20' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	17.0	3"
H-6CW-0425	Fume-A-Vent 4" x 25' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	21.3	3"
H-6CW-0430	Fume-A-Vent 4" x 30' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	25.5	3"
H-6CW-0515	Fume-A-Vent 5" x 15' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	14.3	3.5"
H-6CW-0520	Fume-A-Vent 5" x 20' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	19.0	3.5"
H-6CW-0525	Fume-A-Vent 5" x 25' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	23.8	3.5"
H-6CW-0530	Fume-A-Vent 5" x 30' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	28.5	3.5"
H-6CW-0615	Fume-A-Vent 6" x 15' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	15.0	4.5"
H-6CW-0620	Fume-A-Vent 6" x 20' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	20.0	4.5"
H-6CW-0625	Fume-A-Vent 6" x 25' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	25.0	4.5"
H-6CW-0630	Fume-A-Vent 6" x 30' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	30.0	4.5"
H-6CW-0815	Fume-A-Vent 8" x 15' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	16.5	5"
H-6CW-0820	Fume-A-Vent 8" x 20' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	22.0	5"
H-6CW-0825	Fume-A-Vent 8" x 25' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	27.5	5"
H-6CW-0830	Fume-A-Vent 8" x 30' Type 6CW 600°F Double-Ply Silicone Coated Fiberglass	32.0	5"