

Fume A-Vent Spring Balancer Overhead Exhaust System

Date 7/12


Part No.SDB-XXX

Balancer Simple Drops

TAB 2-F

Fume-A-Vent Overhead Systems are the user-friendly and cost-effective solution that meets a wide variety of demands. The Spring Balancer systems can incorporate many hose types and lifting configurations, all made in the U.S.A. Exhaust Hoses range from high-temperature silicone to medium-temperatures polyester. Our Spring Balancer Systems are a higher end system, known for usability, and high durability. We also offer ductwork, blower fans, and tailpipe adaptor to complete the system.

- 1) Fabric Hose Connects Directly to Ductwork.
- 2) Balancer is Mounted to Ceiling Above
- 3) Fabric Hose Is Positioned Aside From Work Area
- 4) Tailpipe Adaptors Connect Directly to Fabric Hose



All Dimensions in INCHES (mm)



FUME-A-VENT
EXHAUST REMOVAL SYSTEMS
A Product of Air Cleaning Specialists, Inc.

AIR CLEANING SPECIALISTS, INC.
11088 Gravois Industrial Ct. St. Louis MO 63128
866 455-2132 Fax 636 349-0556
www.fume-a-vent.com info@fume-a-vent.com

This sheet has been copyrighted
and is the property of
Air Cleaning Specialists, Inc.

Fume-A-Vent Type 5CW 500°F Single-Ply Silicone Coated Fiberglass Hose

Date 2/14

Part No. H-05CW-XXXX

Type 5CW 500°F Hose

TAB 1-E-2

Fume-A-Vent Type 5CW Hose is specially designed with Exhaust Removal in mind. It can be used on Hose Reels, Simple Drop Systems, and medium to light duty car exhaust removal. This hose features a ThermoPlastic Helix Abrasion Protector, to prevent damage to vehicles or equipment. Standard color is a Silver Hose with Black Helix Protector.

Temperature Range: -50°F to +550°F

This product passed UL-94,V-O standards for flame resistance.

This product has an overall temperature of 550°F when used with a Exhaust Fan.

This hose is made with a Flame Resistant Single-Ply Silicone Coated Fiberglass Hose. The exterior helix deign makes great flow characteristics. The hose is made of a gray fabric with a galvanized steel helix. It has a high compressibility rate and flexibility.

Other information including wall thickness and helix pitch are available upon request. Common lengths shown below include 15' to 35' with 3" to 8" Diameters. Other size options are always available upon request.



Part No	Description	Wt. Lbs.	Bend Radius
H-05CW-0415	4" x 15' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	11.70	3"
H-05CW-0420	4" x 20' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	15.60	3"
H-05CW-0425	4" x 25' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	19.50	3"
H-05CW-0430	4" x 30' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	23.40	3"
H-05CW-0515	5" x 15' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	11.55	3.5"
H-05CW-0520	5" x 20' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	15.40	3.5"
H-05CW-0525	5" x 25' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	19.25	3.5"
H-05CW-0530	5" x 30' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	23.10	3.5"
H-05CW-0615	6" x 15' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	10.50	4.5"
H-05CW-0620	6" x 20' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	14.00	4.5"
H-05CW-0625	6" x 25' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	17.50	4.5"
H-05CW-0630	6" x 30' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	21.00	4.5"
H-05CW-0815	8" x 15' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	18.45	5.5"
H-05CW-0825	8" x 25' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	24.60	5.5"
H-05CW-0830	8" x 30' Type 5CW 500 ⁰ Single-Ply Silicone Coated Fiberglass Hose	30.75	5.5"